

19,5x8,25" **FORGED LIGHT ALLOY WHEEL**

BOLT HOLE Ø 26, 30, 32 MM

ET	146 mm
Max payload	3150 kg
Average weight	18,6 kg
Centre Bore Ø	221 mm
Mounting hole PCD Ø	275 mm
Number of mounting holes	8
Disk thickness	21,0 mm
Half dual Space	167 mm
Twin fitment	yes
N° ABE (Germany)	KBA 51417



Denomination	Surface finish	Bolt hole Ø	Sleeve nut Single	Sleeve nut Twin	Valve code
4015 CM	Diamond	26 mm	~	~	SLT 003
4015 AM	Diamond	30 mm	~	~	SLT 003
4015 BM	Diamond	32 mm	~	~	SLT 003

Material

Approved tire sizes

Locking torque of the valve

Maximum tyre pressure

Approved balance weights

Warranty

SPEEDLINE TRUCK S.r.l.

Viale 1° Maggio 30
24030 Presezzo (BG), Italy

T: +39 035 4158211

E: sales.truck@ronalgroup.com

speedline-truck.com

All information is subject to change. SPEEDLINE TRUCK reserves the right to make changes in design and technical characteristics. The wheel designs and the content of this product information are protected by copyright. Version 13.0

RONALGROUP