

19,5x14,00" FORGED LIGHT ALLOY WHEEL

SLT X SD BOLZENLOCH Ø 26, 32 MM

ET	120 mm
Max. Traglast	5000 kg
Durchschn. Gewicht	23,0 kg
Mittenloch Ø	281 mm
Lochkreisdurchmesser Ø	335 mm
Anzahl Befestigungslöcher	10
Schüsselstärke	29,0 mm
Halber Mittenabstand	~ mm
Zwillingsmontage	nein
ABE-Nr. (Deutschland)	KBA 51970



Artikel Nr.	Oberfläche	Bolzenloch Ø	Schafmutter Einzel	Schafmutter Zwilling	Ventilnummer
X AM sub produkt bsp.	Diamond	26 mm	~	~	SLT 008
X BM	Mirror	32 mm	SLT 979 (M22x1,5), SLT 983 (7/8"11 BSF)	~	SLT 008

Material	IT Not lacquered, highly corrosion resistant alloy, T6061
Zugelassene Reifengröße	IT e.g. 4425/65 R19,5 435/50 R19,5 445/45 R19,5 445/65 R19,5
Anzugsdrehmoment des Ventils	IT 5 Nm for original SPEEDLINE TRUCK valve
Maximaler Reifenfülldruck	IT 9 bar or the lower value recommended by the tire producer
Zugelassene Auswuchtgewichte	IT Clip on and adhesive weights for alloy wheels for commercial vehicles
Garantie	IT 5 years from the manufacturing date without mileage limitation

Dummy PDF file